

PRODUCT DATA

7^{07 19 19} Water
Repellents**ENVIROSEAL[®] G**

Clear, reactive silicate water repellent

Description

Enviroseal[®] G is a clear, penetrating, water-based silicate water-repellent sealer designed for concrete and aged limestone. It prevents water penetration and reduces freeze/thaw damage while allowing surfaces to breathe.

Yield

200 – 300 ft²/gal (4.9 – 7.4 m²/L); varies with porosity of surface

Packaging

5 gallon (19 L) cans

Color

Clear

Shelf Life

1 year when properly stored.

Storage

Store in unopened containers in a cool, clean, dry area. Protect from freezing. Frozen material should be placed in a warm spot to thaw. Do not force thawing by direct heat.

Features

- Penetrating sealer
- Water repellent
- Breathable
- Water based

Benefits

- Helps maintain clean substrate overtime
- Helps prevent rain water penetration
- Allows interior moisture vapor to escape
- Zero VOC—Environmentally friendly

Where to Use

APPLICATION

- Concrete driveways and walks
- Concrete pavers

LOCATION

- Horizontal and vertical
- Interior or exterior

SUBSTRATE

- Concrete
- Aged limestone
- Aged quarried stone

How to Apply**Surface Preparation**

1. All surfaces must be structurally sound, clean, fully cured (28 days), and free of all dust, dirt, bitumens, efflorescence, oil, pollution deposits, all curing, forming, and parting compounds, and all other foreign matter. New stone should age a minimum of 1 year before sealing.
2. Complete all caulking, pointing, or restoration work before application and allow to cure. If application must precede such work, carefully avoid application of Enviroseal[®] G to joint faces. Contamination may cause sealant adhesion problems.
3. For blemish-free or stain-free results, especially on light-colored or white surfaces, surface cleanliness is critical.
4. Surface must be dry and free of frost. After rainfall, allow surface to dry 2 – 3 days or longer to avoid a hazing effect.

Application

1. Apply when surface and air temperatures are above 40° F (4° C) and below 90° F (32° C).
2. Apply directly from the container using a good quality brush, roller, or low-pressure sprayer.
3. For vertical substrates saturate the surface from the bottom up, obtaining a 6 – 12" rundown.
4. Apply to horizontal surfaces in a uniform manner in sufficient quantity to completely wet out the substrate.
5. Care should be taken to treat in 1 coat prior to drying. Enviroseal[®] G will repel additional applications.

Clean Up

Clean all tools and equipment directly after use with soap and water.

For Best Performance

- Slight darkening might occur on some limestones containing slate or iron
- Certain combinations of aggregates, cements, and manufacturing processes may cause Enviroseal[®] G to darken or excessively highlight substrates; darkening or highlighting may particularly be a problem with colored concrete.
- A test application is recommended to determine coverage rate, water repellence, and appearance. Allow 7 days for test verification.

Technical Data

Composition

Enviroseal® G contains water and silicate.

Typical Properties

PROPERTY	VALUE
Total solids and active ingredients by weight, %	7
Specific gravity, g/cc	1.0

- Protect incidental glass, metal, and plastic building components, including polystyrene beadboard and fiberglass. If over spray occurs, remove immediately, preferably with soapy water. Do not allow the material to dry.
- To prevent damage to nearby shrubbery and landscaping, cover or protect with drop cloth.
- Do not apply during inclement weather or if rain is expected within 8 hours.
- Do not use on previously painted surfaces.
- Not recommended for application to aluminum plastics, foam insulation, or any EIFS system.
- Do not use Enviroseal® G on brick, freshly quarried stone, or slate.
- Will not inhibit water penetration through unsound or cracked surfaces or areas with defective flashing, caulking, or structural waterproofing.
- Enviroseal® G is a water-repellent system; where a waterproofing system is required, contact Technical Service for recommendation on proper products.
- Make certain the most current versions of product data sheet and MSDS are being used; call Customer Service (1-800-433-9517) to verify the most current version.
- Proper application is the responsibility of the user. Field visits by BASF personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the jobsite.

Health and Safety

ENVIROSEAL® G

Warning

Enviroseal® G contains potassium methylsilicoate.

Risks

May be irritating to the eyes and skin. Inhalation of vapors may cause irritation to nose, throat and lungs.

Precautions

KEEP OUT OF THE REACH OF CHILDREN. Use appropriate personal protective equipment while mixing or handling this product. Avoid contact with skin and eyes. Use splashproof goggles or other protective eyewear meeting the most current ANSI Z87.1 standards. Use impervious gloves while handling. Use in ventilated area. If poor ventilation exists, use organic vapor or similar type NIOSH approved respirator.

First Aid

In case of eye or skin contact, flush eyes or exposed area thoroughly with water. If irritation persists call a physician. If swallowed, CALL A PHYSICIAN IMMEDIATELY. Only induce vomiting at the instruction of a physician. NEVER GIVE ANYTHING BY MOUTH TO

AN UNCONSCIOUS PERSON. Use in a well ventilated area. Avoid breathing mists and vapors. If needed use a MSHA/NIOSH approved respirator.

Spills/Storage

Use mild acid solution (acetic acid) to neutralize spills. Clean up spills using sand or other inert materials. Keep spills out of sewers and bodies of water. Material is non-combustible. For further information and handling instructions read the appropriate Hydrozo System Products Material Safety Data Sheet.

Refer to Material Safety Data Sheet (MSDS) for further information.

Proposition 65

This product does not knowingly contain chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

VOC Content

0 lbs/gal or 0 g/L, less water and exempt solvents.

**For medical emergencies only,
call ChemTrec (1-800-424-9300).**

BASF Construction Chemicals, LLC – Building Systems

889 Valley Park Drive
Shakopee, MN, 55379

www.BuildingSystems.BASF.com

Customer Service 800-433-9517
Technical Service 800-243-6739



LIMITED WARRANTY NOTICE Every reasonable effort is made to apply BASF exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, BASF MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and BASF shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the BASF Technical Manager.

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF disclaims all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

For professional use only. Not for sale to or use by the general public.

Form No. 1019098 8/07
Printed on recycled paper including 10% post-consumer fiber.

© 2007 BASF
Printed in U.S.A.