

**DYMONIC ALUMINUM STONE**Version 1.2  
REVISION DATE: 09/01/2006

Print Date 09/11/2006

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : DYMONIC ALUMINUM STONE  
 Product code : 955851 323

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Aluminum/Gray. Paste. Vapor may irritate respiratory tract. May cause nausea, headaches, and dizziness. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : Vapor may irritate respiratory tract. May cause nausea, headaches, and dizziness.  
 Eyes : Direct contact may cause mild irritation. May cause temporary injury.  
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged or repeated exposure may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney, and testes damage. Toluene overexposure may cause burns of the skin, respiratory tract damage. May be harmful to the human fetus based on animal tests and limited epidemiology data. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

**Target Organs:** Skin, Eye, Ingestion, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Polyurethane Polymer	NJ TSRN# 51721300-5000P	30.0 - 60.0
Calcium Carbonate (Limestone)	1317-65-3	10.0 - 30.0
Calcium salt	7778-18-9	10.0 - 30.0
Dipropylene glycol dibenzoate	27138-31-4	7.0 - 13.0
Castor oil derivative/modified castor oil	NJ TSRN# 51721300-5008P	5.0 - 10.0
Calcined clay	66402-68-4	3.0 - 7.0
Toluene	108-88-3	1.0 - 5.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Diisodecyl phthalate	26761-40-0	1.0 - 5.0

**DYMONIC ALUMINUM STONE**Version 1.2  
REVISION DATE: 09/01/2006

Print Date 09/11/2006

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form.
- Protective equipment for firefighters : Water may be used to cool containers to minimize pressure build-up. Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapor concentrations in enclosed areas may ignite explosively. Vapors may travel to sources of ignition and flashback.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Store under dry warehouse conditions away from heat and all ignition sources. Store in a cool, well ventilated area. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protection equipment**

## DYMONIC ALUMINUM STONE

Version 1.2

Print Date 09/11/2006

REVISION DATE: 09/01/2006

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Chemical splash goggles.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

### Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA:	5 mg/m3 15 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Calcium salt	7778-18-9	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction.
Toluene	108-88-3	ACGIH TWA: OSHA TWA:	50 ppm 200 ppm	
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Paste
- Color : Aluminum/Gray
- Odor : Ester
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.

**DYMONIC ALUMINUM STONE**

Version 1.2

Print Date 09/11/2006

REVISION DATE: 09/01/2006

Water solubility : Negligible  
Specific Gravity : 1.28  
% Volatile Weight : 3 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Epoxy curing agents.Amines and oxidizing agents.  
Stability : Material is stable under normal storage, handling, and use.  
Hazardous polymerization : Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Toluene, CAS-No.: 108-88-3  
Acute oral toxicity (LD-50 oral) 2,600 - 7,500 mg/kg ( Rat )  
Acute inhalation toxicity (LC-50) 26,700 mg/l ( Rat )  
Acute dermal toxicity (LD-50 dermal) 12,124 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Recycle or dispose of in compliance with local, provincial and federal regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : Toluene 108-88-3

SARA 311/312 Hazards : Acute Health Hazard

## OSHA Hazardous Components :

Calcium Carbonate (Limestone) 1317-65-3  
Calcium salt 7778-18-9

**DYMONIC ALUMINUM STONE**

Version 1.2

Print Date 09/11/2006

REVISION DATE: 09/01/2006

Toluene 108-88-3  
 Titanium dioxide 13463-67-7

OSHA Status: Considered : Irritant  
 hazardous based on the  
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 50 g/l  
 exempt solvent)

VOC Method 310 : 2 %

**U.S. State Regulations:**

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
 Calcium salt 7778-18-9  
 Toluene 108-88-3  
 Titanium dioxide 13463-67-7

Penn RTK Components : Polyurethane Polymer NJ TSRN# 51721300-5000P  
 Calcium Carbonate (Limestone) 1317-65-3  
 Calcium salt 7778-18-9  
 Dipropylene glycol dibenzoate 27138-31-4  
 Castor oil derivative/modified castor oil NJ TSRN# 51721300-5008P  
 Calcined clay 66402-68-4  
 Toluene 108-88-3  
 Titanium dioxide 13463-67-7  
 Diisodecyl phthalate 26761-40-0

NJ RTK Components : Polyurethane Polymer NJ TSRN# 51721300-5000P  
 Calcium Carbonate (Limestone) 1317-65-3  
 Calcium salt 7778-18-9  
 Dipropylene glycol dibenzoate 27138-31-4  
 Castor oil derivative/modified castor oil NJ TSRN# 51721300-5008P  
 Toluene 108-88-3

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:

108-88-3 Toluene  
 14808-60-7 Crystalline Silica (Quartz)/ Silica Sand  
 1333-86-4 Carbon Black  
 71-43-2 Benzene

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	1
Reactivity	1
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe



**DYMONIC ALUMINUM STONE**

Version 1.2

Print Date 09/11/2006

REVISION DATE: 09/01/2006

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
DOT - Department of Transportation  
DSL - Domestic Substance List  
EPA - Environmental Protection Agency  
HMIS - Hazardous Materials Information System  
IARC - International Agency for Research on Cancer  
MSHA - Mine Safety Health Administration  
NDSL - Non-Domestic Substance List  
NIOSH - National Institute for Occupational Safety and Health  
NTP - National Toxicology Program  
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
RCRA - Resource Conservation and Recovery Act  
RTK - Right To Know  
SARA - Superfund Amendments and Reauthorization Act  
STEL - Short Term Exposure Limit  
TLV - Threshold Limit Value  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average  
V - Volume  
VOC - Volatile Organic Compound  
WHMIS - Workplace Hazardous Materials Information System